## VELOCITY TOOLING FOR OKUMA GENOS L300/L3000 BMT

## Live Tools

## 

Notes

## GENOS L300/L3000 ±90° Adjustable Angle Tool • ERAX-20 Output

Wrenches Included with Tools				
Maximum Drill Ø	Maximum Mill Ø			
1/2"	1/4"			
Turret Plugs	14.430.0.0086.0			

VELOCITY/SU-matic driven tools are greased for life and delivered ready to use - *no run-in required*. All driven tools are CMM inspected and internal coolant tools are pressure tested as a final quality check prior to shipment.

Tool #	Coolant	Output	Rotation (In:Out)	Ratio (In:Out)	Max. RPM	Torque	Spindle Wrench	Collet Wrench
14.826.0.0015.0	EXT	ERAX-20	CCW:CW	1:1	6,000	15 Nm	32 mm	7117.20000

GENOS L300/L3000 MY • L300 MYW Gear Hobbing Tool • 3/4" Arbor					Notes			
	2.87 1.24	2.87 1.24 3.86	D	Wrenches Included with Tools				
4		÷ nf				Maximum H	ob Ø	Max. Gear Quality
				┼┉╫╫╗──┰╶╎▁┥А──╟╫╢╢┫╒═┍┍┷┼┼╴╢╴╴┟	80 mm		AGMA 7	
Maximum Hob		5	2.81	4.90	Turret Plu	gs	14.430.0.0086.0	
Diameter: 80mm			<b>VELOCITY/SU-matic</b> driven tools are greased for life and delivered ready to use - <i>no run-in required</i> . All driven tools are CMM inspected and internal coolant tools are pressure tested as a final quality check prior to shipment.					
Tool #	Coolant	Arbor Diameter	Rotation (In:Out)	Ratio (In:Out)	Max. RPM	Torque		3/4" Arbor
14.800.0.0228.0	EXT	3/4"	CW:CCW	2:1	3,000	50 Nm		14.420.0.0126.0

