## VELOCITY TOOLING FOR OKUMA LB2000/LB3000 M/MY/MYW

# **Static Tools**

## 


### LB2000 M / LB3000 M Boring Bar Holders

Reversible

(Main/Sub)

Yes

Yes



Tool #

14.910.0.0214.0


14.910.0.0208.0

Lathe

Model

LB2000 M

I B3000 M



### Notes

Height		VELOCITY/SU-matic ID holders can be used with both internal and external coolant. Internal Coolant Plates are included with all VELOCITY/SU-matic multitasking turret ID holders.	
		Turret Plugs	14.430.0.0086.0
		VELOCITY/SU-matic tooling for OKUMA is manufactured on OKUMA machine tools.	
		Coolant filtration is recommended when using ID holders with internal coolant plates.	
Coolant	ID	Height	Depth (Top)
IC/EXT	1.25"	4.53"	2.95"
IC/EXT	1.5"	4.69"	3.27"

#### LB3000 M/MY/MYW 1.5" Full Depth Boring Bar Holder Notes VELOCITY/SU-matic ID holders can be used with both internal and external coolant. 0 000 Internal Coolant Plates are included **ě** • with all VELOCITY/SU-matic multitasking turret ID holders. Turret Plugs 14.430.0.0086.0 Ш .65 5.24 VELOCITY/SU-matic tooling for OKUMA is manufactured on OKUMA machine tools. Coolant filtration is recommended C when using ID holders with internal 0 coolant plates. Lathe Reversible Tool # Coolant ID Height Depth Model (Main/Sub) LB3000 M 14.910.0.0376.0 IC/EXT 1.5" 4.69" 5.24"

