## VELOCITY TOOLING FOR OKUMA LB2000/LB3000 M/MY/MYW

## **Static Tools**

LB3000 M/MY/MYW 2" Full Depth Boring Bar Holder

## 

Notes

R	lo l			VELOCITY/SU-matic ID holders can be used with both internal and external coolant. Internal Coolant Plates are included with all VELOCITY/SU-matic multitasking turret ID holders.		
					Turret Plugs	14.430.0.0086.0
a start					VELOCITY/SU-matic tooling for OKUMA is manufactured on OKUMA machine tools.	
					Coolant filtration is recommended when using ID holders with internal coolant plates.	
Lathe Model	Tool #	Reversible (Main/Sub)	Coolant	ID	Height	Depth
LB3000 M	14.910.0.0247.2	-	IC/EXT	2"	4.11"	5.24"
LB3000 MYW 1" & 1.5" Boring Bar Holder						
	LB3000 MYW	1" & 1.5" Borin	g Bar Holder		No	tes
	LB3000 MYW	1" & 1.5" Boring		.76 5.61 3.54	VELOCITY ID holders can be us and extern Internal Coolant F	V/SU-matic and with both internal al coolant. Plates are included VTY/SU-matic
	LB3000 MYW				VELOCITY ID holders can be us and extern Internal Coolant F with all VELOCI	V/SU-matic and with both internal al coolant. Plates are included VTY/SU-matic
				3.54 3.54	VELOCITY ID holders can be us and extern Internal Coolant F with all VELOCI multitasking tu	M/SU-matic   aed with both internal   al coolant.   Plates are included   TY/SU-matic   rret ID holders.   14.430.0.0086.0   U-matic   tooling   manufactured on
				2.91 3.54	VELOCITY ID holders can be us and extern Internal Coolant F with all VELOCI multitasking tur Turret Plugs VELOCITY/SU for OKUMA is OKUMA n	Y/SU-matic   eed with both internal   hal coolant.   Plates are included   TY/SU-matic   rret ID holders.   14.430.0.0086.0   U-matic   tooling   manufactured on   nachine tools.   is recommended   Iders with internal
Lathe				2.91 3.54	VELOCITY ID holders can be us and extern Internal Coolant F with all VELOCI multitasking tu Turret Plugs VELOCITY/SU for OKUMA is OKUMA in Coolant filtration when using ID ho	Y/SU-matic   eed with both internal   hal coolant.   Plates are included   TY/SU-matic   rret ID holders.   14.430.0.0086.0   U-matic   tooling   manufactured on   nachine tools.   is recommended   Iders with internal

