
VELOCITY TOOLING FOR OKUMA 2SP-H/2SP-HM Series

2SP-250H/HM Tools



2SP-250H/HM ID Holder




Tool #

14.910.0.0452.0

0

2SP-250H/H



VELOCITY/SU-matic ID holders can be used with both internal and external coolant.

coolont plates

Notes

		Internal Coolant Plates are included with all VELOCITY/SU-matic multitasking turret ID holders.	
		Turret Plugs	14.430.0.0205.0
		VELOCITY/SU-matic tooling for OKUMA is manufactured on OKUMA machine tools.	
		Coolant filtration is recommended when using ID holders with internal coolant plates.	
Reversible Main/Sub)	Coolant	ID	
No	IC/EXT	1.5"	
M Offset ID Hold	ler	No	tes
			al coolant. P lates are included ITY/SU-matic
		VELOCITY ID holders can be us and extern Internal Coolant F with all VELOCI	ed with both internal al coolant. Plates are included TY/SU-matic
		VELOCITY ID holders can be us and extern Internal Coolant F with all VELOCI multitasking tu Turret Plugs	ed with both internal al coolant. Plates are included <i>TY/SU-matic</i> rret ID holders. 14.430.0.0205.0 <i>J-matic</i> tooling manufactured on

			coolant plates.
Tool #	Reversible (Main/Sub)	Coolant	ID
14.910.0.0454.0	No	IC/EXT	1.5"

